



Motor Parameters ILM50x14



PERFORMANCE CHARACTERISTICS (INTERCONNECTION STAR-SERIAL)

Power P	[W]	210
Rated torque T_r	[Nm]	0.54
Peak torque T_{max} @ 20% linearity deviation	[Nm]	1.75
Rated voltage U_r	[V]	48
Rotation speed n_{max}^*	[rpm]	3870
Rated current I_r (phase current amplitude)	[A]	5.3
Copper losses $P_{L,r}$ @ T_r and 20°C	[W]	16.0
Torque constant k_T @ 20°C	[mNm/A]	103
Motor constant k_M @ 20°C	[Nm/√W]	0.136
Terminal resistance R_{TT} @ 20°C	[mΩ]	770
Terminal inductance L_{TT}	[μH]	850
Rotor inertia J	[kgcm ²]	0.090
Number of pole pairs	-	10
Max. efficiency η	%	87
Weight m	[g]	135

* Theoretical no-load rotation speeds at rated voltage U_r . Variations can arise from operation with different inverters. Higher rotation speeds or change of the voltage level can be achieved by varying the interconnection scheme.

MAXIMAL ROTATION SPEEDS

DC link voltage [V]	48	36	24	14	12	9
star-serial n_{max}^* [rpm]	3870	2900	1940	1160	970	730
delta-serial n_{max}^* [rpm]	6700	5030	3350	2010	1680	1260
star-parallel n_{max}^* [rpm]	7740	5810	3870	2320	1940	1450
delta-parallel n_{max}^* [rpm]	13400**	10050	6700	4020	3350	2510

* Theoretical no-load rotation speeds at indicated voltage. Mechanical limits apply and must not be exceeded. Variations can arise from operation with different inverters.


** $n_{max, mech} = 12000$ rpm must not be exceeded.

CHARACTERISTICS INTERCONNECTION VARIANTS


Interconnection	U_r [V]	I_r [A]	k_T [mNm/A]	R_{TT} [mΩ]	L_{TT} [μH]
star-serial	48	5.3	103	770	850
delta-serial	28	9.2	59	257	283
star-parallel	24	10.6	52	193	213
delta-parallel	14	18.4	30	64	71

AVAILABLE INTERCONNECTION VARIANTS


Star-serial




Delta-serial




Star-parallel




Delta-parallel




T/N-DIAGRAM ILM50X14 STAR-SERIAL @ 22 °C




T/I-DIAGRAM ILM50X14 STAR-SERIAL @ 22 °C




T/N-DIAGRAM ILM50X14 DELTA-SERIAL @ 22 °C




T/I-DIAGRAM ILM50X14 DELTA-SERIAL @ 22 °C




T/N-DIAGRAM ILM50X14 STAR-PARALLEL @ 22 °C




T/I-DIAGRAM ILM50X14 STAR-PARALLEL @ 22 °C



T/N-DIAGRAM ILM50X14 DELTA-PARALLEL @ 22 °C



T/I-DIAGRAM ILM50X14 DELTA-PARALLEL @ 22 °C



FOR FURTHER INQUIRIES, PLEASE CONTACT:

TQ-SYSTEMS GMBH

Gut Delling, Mühlstraße 2
82229 Seefeld
Deutschland

Tel.: +49 8153 9308-0

Fax: +49 8153 4223

E-Mail: info@tq-robodrive.com

Internet: www.tq-group.com

© TQ-Systems GmbH 2021 | All data is for information purposes only | Subject to change without notice | DRVA_DB-ILM-Kits_ILM50x14_Rev200