



Motor Parameters ILM70x18



PERFORMANCE CHARACTERISTICS (INTERCONNECTION STAR-SERIAL)

Power P	[W]	270
Rated torque T_r	[Nm]	1.24
Peak torque T_{max} @ 20% linearity deviation	[Nm]	4.05
Rated voltage U_r	[V]	48
Rotation speed n_{max}^*	[rpm]	2120
Rated current I_r (phase current amplitude)	[A]	6.7
Copper losses $P_{L,r}$ @ T_r and 20°C	[W]	22.2
Torque constant k_T @ 20°C	[mNm/A]	187
Motor constant k_M @ 20°C	[Nm/√W]	0.266
Terminal resistance R_{TT} @ 20°C	[mΩ]	660
Terminal inductance L_{TT}	[μH]	1460
Rotor inertia J	[kgcm ²]	0.321
Number of pole pairs	-	10
Max. efficiency η	%	90
Weight m	[g]	330

* Theoretical no-load rotation speeds at rated voltage U_r . Variations can arise from operation with different inverters. Higher rotation speeds or change of the voltage level can be achieved by varying the interconnection scheme.

MAXIMAL ROTATION SPEEDS

DC link voltage [V]	48	36	24	14	12	9
star-serial n_{max}^* [rpm]	2120	1590	1060	640	530	400
delta-serial n_{max}^* [rpm]	3670	2750	1840	1100	920	690
star-parallel n_{max}^* [rpm]	4240	3180	2120	1270	1060	800
delta-parallel n_{max}^* [rpm]	7340	5510	3670	2200	1840	1380


* Theoretical no-load rotation speeds at indicated voltage. Mechanical limits apply and must not be exceeded. Variations can arise from operation with different inverters.

CHARACTERISTICS INTERCONNECTION VARIANTS


Interconnection	U_r [V]	I_r [A]	k_T [mNm/A]	R_{TT} [mΩ]	L_{TT} [μH]
star-serial	48	6.7	187	660	1460
delta-serial	28	11.6	108	220	487
star-parallel	24	13.4	94	165	365
delta-parallel	14	23.2	54	55	122

AVAILABLE INTERCONNECTION VARIANTS


Star-serial




Delta-serial




Star-parallel




Delta-parallel




T/N-DIAGRAM ILM70X18 STAR-SERIAL @ 22 °C




T/I-DIAGRAM ILM70X18 STAR-SERIAL @ 22 °C




T/N-DIAGRAM ILM70X18 DELTA-SERIAL @ 22 °C




T/I-DIAGRAM ILM70X18 DELTA-SERIAL @ 22 °C




T/N-DIAGRAM ILM70X18 STAR-PARALLEL @ 22 °C




T/I-DIAGRAM ILM70X18 STAR-PARALLEL @ 22 °C



T/N-DIAGRAM ILM70X18 DELTA-PARALLEL @ 22 °C



T/I-DIAGRAM ILM70X18 DELTA-PARALLEL @ 22 °C



FOR FURTHER INQUIRIES, PLEASE CONTACT:

TQ-SYSTEMS GMBH

Gut Delling, Mühlstraße 2
82229 Seefeld
Deutschland

Tel.: +49 8153 9308-0

Fax: +49 8153 4223

E-Mail: info@tq-robodrive.com

Internet: www.tq-group.com

© TQ-Systems GmbH 2021 | All data is for information purposes only | Subject to change without notice | DRVA_DB-ILM-Kits_ILM70x18_Rev200