



Motor Parameters ILM85x13



PERFORMANCE CHARACTERISTICS (INTERCONNECTION STAR-SERIAL)

Power P	[W]	440
Rated torque T_r	[Nm]	1.44
Peak torque T_{max} @ 20% linearity deviation	[Nm]	4.66
Rated voltage U_r	[V]	48
Rotation speed n_{max}^*	[rpm]	2950
Rated current I_r (phase current amplitude)	[A]	10.8
Copper losses $P_{L,r}$ @ T_r and 20°C	[W]	19.3
Torque constant k_T @ 20°C	[mNm/A]	134
Motor constant k_M @ 20°C	[Nm/√W]	0.330
Terminal resistance R_{TT} @ 20°C	[mΩ]	220
Terminal inductance L_{TT}	[μH]	560
Rotor inertia J	[kgcm ²]	0.61
Number of pole pairs	-	10
Max. efficiency η	%	92
Weight m	[g]	400

* Theoretical no-load rotation speeds at rated voltage U_r . Variations can arise from operation with different inverters. Higher rotation speeds or change of the voltage level can be achieved by varying the interconnection scheme.

MAXIMAL ROTATION SPEEDS

DC link voltage [V]	48	36	24	14	12	9
star-serial n_{max}^* [rpm]	2950	2210	1480	890	740	550
delta-serial n_{max}^* [rpm]	5100	3830	2550	1530	1280	960
star-parallel n_{max}^* [rpm]	5900	4430	2950	1770	1480	1110
delta-parallel n_{max}^* [rpm]	10200**	7650	5100	3060	2550	1910

* Theoretical no-load rotation speeds at indicated voltage. Mechanical limits apply and must not be exceeded. Variations can arise from operation with different inverters.


** $n_{max,mech} = 7900$ rpm must not be exceeded.

CHARACTERISTICS INTERCONNECTION VARIANTS


Interconnection	U_r [V]	I_r [A]	k_T [mNm/A]	R_{TT} [mΩ]	L_{TT} [μH]
star-serial	48	10.8	134	220	560
delta-serial	28	18.7	77	73	187
star-parallel	24	21.6	67	55	140
delta-parallel	14	37.4	39	18	47

AVAILABLE INTERCONNECTION VARIANTS


Star-serial




Delta-serial




Star-parallel




Delta-parallel




T/N-DIAGRAM ILM85X13 STAR-SERIAL @ 22 °C




T/I-DIAGRAM ILM85X13 STAR-SERIAL @ 22 °C




T/N-DIAGRAM ILM85X13 DELTA-SERIAL @ 22 °C




T/I-DIAGRAM ILM85X13 DELTA-SERIAL @ 22 °C




T/N-DIAGRAM ILM85X13 STAR-PARALLEL @ 22 °C




T/I-DIAGRAM ILM85X13 STAR-PARALLEL @ 22 °C



T/N-DIAGRAM ILM85X13 DELTA-PARALLEL @ 22 °C



T/I-DIAGRAM ILM85X13 DELTA-PARALLEL @ 22 °C



FOR FURTHER INQUIRIES, PLEASE CONTACT:

TQ-SYSTEMS GMBH

Gut Delling, Mühlstraße 2
82229 Seefeld
Deutschland

Tel.: +49 8153 9308-0

Fax: +49 8153 4223

E-Mail: info@tq-robodrive.com

Internet: www.tq-group.com

© TQ-Systems GmbH 2021 | All data is for information purposes only | Subject to change without notice | DRVA_DB-ILM-Kits_ILM85x13_Rev200